



# **VLISSINGSE MOEF WIT®**

## **DESCRIPTION FORM**

The visible brickwork will be carried out in non-perforated, dipped, hand moulded facing brick with distinctive nerve lines. The yellow basic brick is first tumbled to give it a robust and whimsical character. It is then immersed in a clay bath, which gives the entire surface of the brick a frost-resisting top layer in shaded white with full guarantee. Owing to the specific production process, the packs at times contain quarter, half and three quarter bricks also. The colour is shaded white. The bricks are suited for every building style and have the necessary properties required of contemporary facing bricks. In order to protect and guarantee their authenticity, the bricks are registered.

## **VLISSINGSE MOEF WIT®**



### COMPOSED AFTER CE-COMPLIANT FACING BRICKS WITH THE FOLLOWING CHARACTERISTICS

Туре	Facing brick with a traditional appearance
Colour	shaded white
Format (mm)	217/102/65
Number per m² (*)	55
Recommended masonry (**)	Random pattern
Number per pack / weight per pack (kg)	550/1080
Common brick category	I-HD
Size tolerance	T2
Class row	R1
Fire reaction / Euroclass	A1
Soluble salt content	S2
Efflorescence	no efflorescence
Durability / frost resistance	F2 highly frost resistant
Porosity (%)	<= 24
Average compressive strength (N/mm²)	>= 15
Thermal conductivity (W/mK)	0,37

The presented values and colours are only approximtee. To obtain the same colour overall in the brickwork, the bricks from different packs must be mixed together. The complete part of bricks must be delivered at once. Clay bricks may show some slight colour variation per production batch from previous batches. The manufacturer reserves the right to change the product range and the packaging.

<sup>(\*)</sup> Depending on the layer size used (\*\*) see also our installation method