Declaration of performance

number: 2020-004/ev



Evolution Silver Blue

 (4) Manufacturer

 Olivier Bricks NV
 tel: +32 51 26 52 52

 Roeselarestraat 509
 info@olivier.be

 B-8870 Izegem
 www.olivier.be

(1) Unique identification code of the product	Evolution Silver Blue	
(2) Typenumber	Silverblue	
(3) Intended use or uses of the construction product	U units for use in unprotected masonry walls, colums and partitions	
(6) System or systems of assessment and verification	21	
of constancy of perforance of the construction product	4 ⁺	
Composed after CE-compliant facing bricks with the following characteristics		

(9)Declared performance:					
Dimensions					
Length	270	mm			
Width	100	mm			
Height	50	mm			
Dimensional tolerance	T1				
Range category	R1		U		
Flatness of bed faces	NPD		Metselbaksteen,		
Parallellisme bed faces	NPD		Categorie I volgens EN77-		
Gross dry density	1820	kg/m3	1:2011		
Net dry density	NPD	%	+		
Tolerance volumetric mass: class/%	D1 / ±10		A1:2015		
Total volume frog	NPD				
Group Eurocode	1				
Mean compressive strength	>= 25	N/mm2			
Normalised compressive strenght	>= 25	N/mm2			
Bond strenght	>0,15				
Thermal conductivity	0,66	W/mK	EN 1745:2012		
Water vapour permeability	5/10				
Durability : freeze/thaw resistance	F2				
Water absorption	<=12%				
Initial rate of water absorption	NPD	kg/(m2min)			
Active soluble salt content	S2				
Dimensional stability : moisture movement	NPD	mm/m			
Dangerous substance	Suffice		NL-BBK		
Firereaction	A 1				

(10) The performance of the product identified in points (1) en (2) is in conformity with the declared performance in point (9). This declaration of performance is issued under the sole responsibility of the manufacturer identified in point (4). Signed for and on behalf of the manufacturer by

Frederik Ardies

Managing Director

(BE) Izegem 01/01/2020