## **Declaration of performance**

number: 2020-003/tr



## Antwerps Klompje

(4) Manufacturer

Olivier Bricks NV tel: +32 51 26 52 52

Roeselarestraat 509 info@olivier.be

B-8870 Izegem www.olivier.be

(1) Unique identification code of the product	Antwerps Klompje	
(2) Typenumber	00361	
(3) Intended use or uses of the construction product	U units for use in unprotected masonry walls, colums and partitions	
(6) System or systems of assessment and verification	21	
of constancy of perforance of the construction product	<b>2</b> <sup>T</sup>	
Composed after CE-compliant facing bricks with the following characteristics		

(9)Declared performance:			
Dimensions	M50		
Length	188	mm	
Width	88	mm	
Height	48	mm	
Dimensional tolerance	T1		
Range category	R1		U Metselbaksteen,
Flatness of bed faces	NPD		
Parallellisme bed faces	NPD		Categorie I volgens EN77-
Gross dry density	1650	kg/m3	1:2011 +
Net dry density	1700	%	
Tolerance volumetric mass: class/%	D1 / ±10		A1:2015
Total volume frog	NPD		
Group Eurocode	1		
Mean compressive strength	>= 12	N/mm2	
Normalised compressive strenght	>= 12	N/mm2	
Bond strenght	NPD		
Thermal conductivity	0,69	W/mK	EN 1745:2012
Water vapour permeability	5/10		
Durability : freeze/thaw resistance	F2		
Water absorption	<=14%		
Initial rate of water absorption	1,5 - 4	kg/(m2min)	
Active soluble salt content	S2		
Dimensional stability : moisture movement	NPD	mm/m	
Dangerous substance	Suffice		NL-BBK
Firereaction	A1		

(10) The performance of the product identified in points (1) en (2) is in conformity with the declared performance in point (9). This declaration of performance is issued under the sole responsibility of the manufacturer identified in point (4). Signed for and on behalf of the manufacturer by

Frederik Ardies

Managing Director

(BE) Izegem 01/01/2020