## **Declaration of performance**

number: 2023-001/lu



## Lungo Terra

(4) Manufacturer	
Olivier Bricks NV	tel: +32 51 26 52 52
Roeselarestraat 509	info@olivier.be
B-8870 Izegem	www.olivier.be

(1) Unique identification code of the product	Lungo Terra		
(2) Typenumber	LungoTer		
(3) Intended use or uses of the construction produc U units for use in unprotected masonry walls, colums and partitions			
(6) System or systems of assessment and verification of constancy of perforance of the construction product	2+		
Composed after CE-compliant facing bricks with the following characteristics			

(9)Declared performance:				
Dimensions				
Length	288	mm	U Metselbaksteen,	
Width	88	mm		
Height	50	mm		
Dimensional tolerance	T1			
Range category	R2			
Flatness of bed faces	1%			
Parallellisme bed faces	2		Categorie I	
Gross dry density	1375-D2	kg/m3	volgens EN77- 1:2011	
Net dry density	2000-D1	%	+	
Tolerance volumetric mass: class/%	NPD		A1:2015	
Total volume frog	NPF			
Group Eurocode	1			
Mean compressive strength	>= 23	N/mm2		
Normalised compressive strenght	>= 23	N/mm2		
Bond strenght	NPD			
Thermal conductivity	0,44	W/mK	NBN B 27-009	
Water vapour permeability	5/10			
Durability : freeze/thaw resistance	F2			
Water absorption	<=12%			
Initial rate of water absorption/ IW finished product	1,5 - 4 / 0,5 - 1,5	kg/(m2min)		
Active soluble salt content	<b>S</b> 2			
Dimensional stability : moisture movement	NPD	mm/m		
Dangerous substance	Suffice			
Firereaction	A1			

(10) The performance of the product identified in points (1) en (2) is in conformity with the declared performance in point (9). This declaration of performance is issued under the sole responsibility of the manufacturer identified in point (4). Signed for and on behalf of the manufacturer by

Frederik Ardies

Managing Director

(BE) Izegem 01/05/2023